



**EZ-Courts Sport Deck Tile Specifications**

**Description:**

Open grid design measuring 12”x12”1/2” high impact polypropylene copolymer suspended molecules, with ultra high support structure and maximum strength to weight ratio.

**Physical Properties:**

**MATERIAL TEST RESULTS**

- A.Á Rockwell hardness (ASTM D 785): 65
- B.Á Heat deflection@ 66 psi (ASTM E 648): 180
- C.Á Flaming at 1000mm (ASTM E 648): 4 min 30s
- D.Á Auto-ignition temperature (ASTM D-1929): 950° F
- E.Á Vicat softening point (ASTM D-1525): 284° F
- F.Á Low temperature brittleness (ASTM D-2137): -22° F
- G.Á Co-efficient of Linear Thermal Expansion, (ASTM D-696, E-831): 3.3x10-5 (in/in) / ° F
- H.Á E-Modulus (ASTM D-5418) 136,000 psi (850MPa)
- I.Á Flex-Modulus (ASTM D-790) 145,000 psi
- J.Á Tensile Yield Strength (ASTM D-638) 3200 psi
- K.Á Elongation at Yield (ASTMD-638): 18%
- L.Á Notched Izod (ASTM D-256) 18 (ft-lbs / in) at 20° C
- M.Á Ultra Violet (UV) protection 10% max fading over 10 years at 140 kLy exposure

**PRODUCT TEST RESULTS**

- A.Á Flame spread Index (ASTM E-468): 4m55s
- B.Á Smoke Development (ASTM E-162): 2m23s
- C.Á Radiant Panel (ASTM E-84, 162, 648) 0.12 Watts/cm<sup>2</sup>
- D.Á Friction Test (ASTM C-1028) dry < .40 wet < .60
- E.Á Compression vs. crush (ASTM D-3998): no break
- F.Á Noise Reduction Coefficient (ASTM C-423) 20%
- G.Á Rolling Load (DIN 18032) Very Good
- H.Á R-Value < 1.0
- I.Á Flatness +/- 0.02 mm
- J.Á Load Bearing Capacity: 25,000 lbs/sq.ft.

**SANITARY INFORMATION**

- A.Á Resistance to fungi (in compliance with ASTM G-21). Basic organisms test (ATCC #6205) indicates zero growth.
- B.Á Resistance to the following:
  - ✓Á Bacteria and mildew resistance
  - ✓Á Gram-positive bacterial Staphylococcus Aureus
  - ✓Á Gram-negative Klebsiella Pneumoniae
  - ✓Á Pink-staining organism.
  - ✓Á STV Reticulum
  - ✓Á Surface fungi growth prior to and following leaching.

**Warranty:**

**EZ-Courts™** sport tile for courts is warranted for any defects in material and workmanship for a period of 5 years as set forth in the manufacturer’s standard limited warranty.



A  
CWF Flooring, Inc.  
Company



**EZ COURT**  
Sport Tiles

[www.SportTiles.Pro](http://www.SportTiles.Pro)